







RK-EU-FL10

Floodlights



DESCRIPTION:	Surface or ground-mounted LED luminaire Light distribution type : direct Optical system: tempered glass diffuser, impact resistant Housing: aluminium Colour: dark grey, RAL7043
GENERAL DATA:	Mains voltage: 220-240V, 50-60Hz LED lifetime, h: 15000/L70B50 Protection class IEC: I Ingress protection code : IP65 Mechanical impact resistance : IK08 Operating temperature range, °C: ta -25...+40
INSTALLATION:	On the horizonntal or vertical surfaces on the ground. Cable, 0.35m, 3x1.0mm ²
ENVIRONMENT:	Outdoor
APPLICATION:	Facade illumination, park, public space



Apus LED GRO

Apus LED HOL

PRODUCT	DIAMETER, mm	HEIGHT, mm	LUMINAIRE OUTPUT*, lm	SYSTEM POWER*, W	SYSTEM EFFICACY*, lm/W	CRI	CCT*, K	WEIGHT, kg
RK-EU-FL10 1GU10 O11 HOL	98	158						0,4
RK-EU-FL10 1GU10 O12 GRO	98	328						0,4
RK-EU-FL10 1x400 G872 T840 HOL L40	98	158	392	4,2	93	80+	4000	0,4
RK-EU-FL10 1x400 G873 T840 GRO L40	98	328	392	4,2	93	80+	4000	0,4

*Tolerance range for optical and electrical data: -10%. Values apply to an ambient temperature of 25°C. RIKADA is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

OPTIONS AVAILABLE ON REQUEST:

LED	COVERS	COLOUR
T830	LOUVER	RAL
T840		

STANDARD

