

RK-EU-BA11

Batten Lights



DESCRIPTION: Suspended asymmetrical LED batten luminaire
Light distribution type: direct
Optical system: lenses
Housing: steel
Colour: white, RAL9003S

GENERAL DATA: **Mains voltage:** 220-240V, 0/50-60Hz
LED lifetime, h: 100000/L80B10
SDCM: 3
Protection class IEC: I
Ingress protection code: IP20
Mechanical impact resistance: IK05
Operating temperature range, °C: ta 0...+35/+40

INSTALLATION: Suspended (wire, cable and cap to be ordered separately), on the wall (mounting brackets to be ordered separately). Push-in terminal, 3x2x2.5mm²

ENVIRONMENT: Indoor

APPLICATION: Retail, hall, public place



PRODUCT	LENGTH, mm	WIDTH, mm	HEIGHT, mm	LUMINAIRE OUTPUT*, lm	SYSTEM POWER*, W	SYSTEM EFFICACY*, lm/W	CRI	CCT*, K	WEIGHT, kg
RK-EU-BA11 1x3800 J424 T840 L1A18 LO1	1133	47	85	3757	21,8	172	80+	4000	3,7
RK-EU-BA11 1x5250 J425 T840 L1A18 LO2	1133	47	85	5205	31,7	164	80+	4000	3,7
RK-EU-BA11 1x5500 J426 T840 L1A18 LO3	1133	47	85	5465	30,0	182	80+	4000	3,7
RK-EU-BA11 1x6500 J427 T840 L1A18 LO4	1133	47	85	6499	35,9	181	80+	4000	3,7
RK-EU-BA11 1x7500 J428 T840 L1A18 LO5	1133	47	85	7475	41,6	180	80+	4000	3,7
RK-EU-BA11 1x4700 J429 T840 L1A18 LO1	1414	47	85	4696	27,0	174	80+	4000	4,1
RK-EU-BA11 1x6550 J430 T840 L1A18 LO2	1414	47	85	6507	38,7	168	80+	4000	4,1
RK-EU-BA11 1x6850 J431 T840 L1A18 LO3	1414	47	85	6832	36,7	186	80+	4000	4,1
RK-EU-BA11 1x8150 J432 T840 L1A18 LO4	1414	47	85	8123	44,4	183	80+	4000	4,1
RK-EU-BA11 1x9350 J433 T840 L1A18 LO5	1414	47	85	9344	51,5	181	80+	4000	4,1

*Tolerance range for optical and electrical data: -10%. Values apply to an ambient temperature of 25°C. RIKADA is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

AVAILABLE ACCESSORIES:



Product: Suspension MTG KIT SUSI
Description: Suspension wire set "I" type, 1.5m adjustable, 1pcs
**note - 2pcs MTG SUSI KIT for 1 luminaire required*



Product: I-JOIN RK-EU-BA04
Description: I-Join element for connecting luminaires in-line, 1pcs (extra)



Product: CAP4, light grey/ white/ black
Description: Square decorative metal cap for hiding cable inlet with suspension wire attachment point, push-in terminals 3x1x1.5mm², light grey/ white/ black

Product: CAP5, light grey/ white/ black
Description: Square decorative metal cap for hiding cable inlet with suspension wire attachment point, push-in terminals 5x1x1.5mm², light grey/ white/ black



Product: WALL MTG KIT RK-EU-BA11 RAL9003S
Description: Support bracket for luminaire installation onto wall. 2pcs



Product: CAP cable 3x0.75 2.0m clear
Description: Cable 3x0.75mm² for suspended luminaire up to 2.0 meters, transparent



Product: CAP cable clip D6.3mm SET clear
Description: Cable and suspension wire clip set, 4pcs. For cable diameter up to 6,3mm and wire diameter 1mm

OPTIONS AVAILABLE ON REQUEST:

LED	CONTROL GEAR	EMERGENCY	CONNECTION	COLOUR
T830	DALI	EM3 ¹	CBF3-2.0m clear	RAL
T840		EM3A ¹	CBF3-3.0m clear	
		EM3D ¹	CBF5-2.0m clear	
			CBF5-3.0m clear	

¹ Operating temperature range for Luminaires with EM option, °C: ta 0... +35

L1A18

