

RK-EU-SPT12

Spotlights





DESCRIPTION: Recessed mounted adjustable LED spotlight
Light distribution type: direct
Optical system: faceted aluminium reflector, 60°, tempered glass diffuser
Housing: aluminium
Colour: white, RAL9016

GENERAL DATA: Mains voltage: 220-240V, 0/50-60Hz
LED lifetime, h: 60000/L80B10
SDCM: 3
Protection class IEC: II
Ingress protection code: IP40
Mechanical impact resistance: IK02
Operating temperature range, °C: ta 0...+35

INSTALLATION: In ceilings with cut-out openings (mounting brackets included). Push-in terminal, 2x1x1.5mm²

ENVIRONMENT: Indoor

APPLICATION: Retail, showroom, exhibition, public place



PRODUCT	DIAMETER, mm	HEIGHT, mm	CUT-OUT, mm	LUMINAIRE OUTPUT*, lm	SYSTEM POWER*, W	SYSTEM EFFICACY*, lm/W	CRI	CCT*, K	WEIGHT, kg
RK-EU-SPT12 1x1850 E826 T840 R60	180	147	170	1857	13,5	138	80+	4000	2,5
RK-EU-SPT12 1x2450 E827 T840 R60	180	147	170	2523	18,7	135	80+	4000	2,5
RK-EU-SPT12 1x3250 D784 T840 R60	180	147	170	3397	26,5	128	80+	4000	2,5
RK-EU-SPT12 1x4150 J210 T840 R60	180	147	170	4261	35,1	121	80+	4000	2,5
RK-EU-SPT12 1x4650 D785 T840 R60	180	147	170	4867	40,2	121	80+	4000	2,5
RK-EU-SPT12 1x5050 D786 T840 R60	180	147	170	5413	46,6	116	80+	4000	2,5

*Tolerance range for optical and electrical data: -10%. Values apply to an ambient temperature of 25°C. RIKADA is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

OPTIONS AVAILABLE ON REQUEST:

LED	CONTROL GEAR	EMERGENCY	CONNECTION	COLOUR
T830	DALI	EM3	WIE3-0.5m	RAL
T840		EM3A	WIE5D-0.5m	
T930		EM3D	Europlug-1.5m	
T940			Europlug-3.0m	
T820 MEAT				
T831 MEAT&WHITE				
T825 BREAD				
T930 VEGETABLES				
T932 FASHION				
T931 FASHION&WHITE				
T927 NATURAL				
T930 NATURAL				
T940 NATURAL				

R60

