




RK-EU-WL04



Wall Lights



DOWN



2x



DESCRIPTION: Surface mounted LED wall washer
Light distribution type: direct/indirect
Optical system: tempered glass diffuser, impact resistant
Housing: aluminium
Colour: dark grey, RAL7043

GENERAL DATA: Mains voltage: 220-240V, 50-60Hz
 LED lifetime, h: 15000/L70B50
 Protection class IEC: I
 Ingress protection code: IP54
 Mechanical impact resistance: IK08
 Operating temperature range, °C: ta -25...+40

INSTALLATION: On the wall. Screw terminal, 3x1x1.5mm²

ENVIRONMENT: Outdoor

APPLICATION: Facade illumination


PRODUCT	LENGTH, mm	DIAMETER, mm	HEIGHT, mm	LUMINAIRE OUTPUT*, lm	SYSTEM POWER*, W	SYSTEM EFFICACY*, lm/W	CRI	CCT*, K	WEIGHT, kg
RK-EU-WL04 2GU10 O13	160	90	300						1,4
RK-EU-WL04 1GU10 O14 UP	160	90	158						1,3
RK-EU-WL04 1GU10 O15 DOWN	160	90	158						1,3
RK-EU-WL04 2x400 G865 T840 L40	160	90	300	794	8,4	95	80+	4000	1,5
RK-EU-WL04 UP 1x400 G866 T840 L40	160	90	158	397	4,2	95	80+	4000	1,4

*Tolerance range for optical and electrical data: -10%. Values apply to an ambient temperature of 25°C. RIKADA is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

OPTIONS AVAILABLE ON REQUEST:

LED	COLOUR
T830	RAL
T840	

2x L40



UP L40

