

RK-EU-SPT13

Spotlights



DESCRIPTION: **Suspended LED spotlight**
Light distribution type: direct
Optical system: faceted aluminium reflector, clear PMMA diffuser
Housing: aluminium
Colour: white, RAL9016; black, RAL9017

GENERAL DATA: **Mains voltage:** 220-240V, 50-60Hz (220-240V, 0/50-60Hz for model J564)
LED lifetime, h: 60000/L80B10
SDCM: 3
Protection class IEC: I
Ingress protection code: IP20
Mechanical impact resistance: IK02
Operating temperature range, °C: ta 0...+35

INSTALLATION: Suspended or surface (cap and cable included). Cable, 1.1m, 3x0.75mm²

ENVIRONMENT: Indoor

APPLICATION: Hotel, retail, showroom, exhibition, public place



PRODUCT	DIAMETER, mm	HEIGHT, mm	LUMINAIRE OUTPUT*, lm	SYSTEM POWER*, W	SYSTEM EFFICACY*, lm/W	CRI	CCT*, K	WEIGHT, kg
RK-EU-SPT13 1x2300 J562 T840 R45	77	245	2276	15,4	148	80+	4000	1,1
RK-EU-SPT13 1x2750 J563 T840 R45	77	245	2734	19,3	142	80+	4000	1,1
RK-EU-SPT13 1x3250 J564 T840 R45	77	245	3217	22,9	140	80+	4000	1,1

*Tolerance range for optical and electrical data: -10%. Values apply to an ambient temperature of 25°C. RIKADA is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification


OPTIONS AVAILABLE ON REQUEST:

	LED	REFLECTOR AND OPTICS	CONTROL GEAR	CONNECTION	OTHER	COLOUR	
	T830	T930 VEGETABLES	R24	DALI ¹	TRACK	SR	RAL
	T840	T932 FASHION	R32		TRACK N m²		
	T930	T931 FASHION&WHITE	R45				
	T940	T927 NATURAL	R55				
	T820 MEAT	T930 NATURAL					
	T831 MEAT&WHITE	T940 NATURAL					
	T825 BREAD						


¹ Stucchi tracks are not compatible with switch-control dimming

² Please specify cable length before placing an order


R24



R32



R45



R55

