

RK-EU-DS13

Diffused Surface Lights



DESCRIPTION: **Wall-mounted decorative LED luminaire**
Light distribution type: direct/indirect
Optical system: opal polycarbonate diffuser
Housing: aluminium
Colour: light grey, RAL9006S;
white, RAL9003S; black, RAL9005S

GENERAL DATA: **Mains voltage:** 220-240V, 0/50-60Hz
LED lifetime, h: 50000/L80B10
SDCM: 3
Protection class IEC: I
Ingress protection code: IP40
Mechanical impact resistance: IK05
Operating temperature range, °C: ta -15...+35

INSTALLATION: On the wall. Push-in terminal, 3x2x2.5mm²

ENVIRONMENT: Indoor

APPLICATION: Hotel, bathroom



PRODUCT	LENGTH, mm	WIDTH, mm	HEIGHT, mm	LUMINAIRE OUTPUT*, lm	SYSTEM POWER*, W	SYSTEM EFFICACY*, lm/W	CRI	CCT*, K	WEIGHT, kg
RK-EU-DS13 1x800/800 D847 T840 OP LG3	580	85	75	1445	12,8	112	80+	4000	2,0
RK-EU-DS13 1x1100/1100 D848 T840 OP LG3	580	85	75	1968	18,0	110	80+	4000	2,0
RK-EU-DS13 1x1500/1500 D849 T840 OP LG3	580	85	75	2705	25,6	105	80+	4000	2,0
RK-EU-DS13 1x1150/1050 J434 T840 OP LG3	860	85	75	2167	19,1	113	80+	4000	2,5
RK-EU-DS13 1x1550/1450 J435 T840 OP LG3	860	85	75	2952	27,0	109	80+	4000	2,5
RK-EU-DS13 1x2150/1950 J436 T840 OP LG3	860	85	75	4058	38,6	105	80+	4000	2,5
RK-EU-DS13 1x1550/1400 J437 T840 OP LG3	1140	85	75	2888	25,1	115	80+	4000	3,0
RK-EU-DS13 1x2100/1900 J438 T840 OP LG3	1140	85	75	3936	31,8	124	80+	4000	3,0
RK-EU-DS13 1x2850/2600 J439 T840 OP LG3	1140	85	75	5411	50,9	106	80+	4000	3,0

*Tolerance range for optical and electrical data : -10%. Values apply to an ambient temperature of 25°C. RIKADA is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

OPTIONS AVAILABLE ON REQUEST:

CONTROL GEAR	COLOUR
DALI	RAL
BLT	

OP



