


RK-EU-PL15

Park and Street Lights



DESCRIPTION:

Suspended LED street luminaire
Light distribution type: direct
Optical system: lenses, tempered glass diffuser, impact resistant
Housing: aluminium
Colour: black grey, RAL7021

GENERAL DATA:

Mains voltage: 220-240V, 0/50-60Hz
LED lifetime, h: 100000/L90B10
SDCM: 5
Protection class IEC: I
Ingress protection code: IP66
Mechanical impact resistance: IK08
Operating temperature range, °C: ta -40...+40

INSTALLATION:



With special bracket on Ø12mm horizontal line.
 Adjustable installation angles: on vertical plane: +/- 30 degrees, on horizontal plane: +/- 30 degrees. Push-in terminal, 3x2x2.5mm²

ENVIRONMENT:

Outdoor

APPLICATION:

Parking area, public space, street



PRODUCT	DIAMETER, mm	HEIGHT, mm	LUMINAIRE OUTPUT*, lm	SYSTEM POWER*, W	SYSTEM EFFICACY*, lm/W	CRI	CCT*, K	WEIGHT, kg
RK-EU-PL15 1x5850 J462 T740 LS140	490	130	5820	36,2	161	70+	4000	8,3
RK-EU-PL15 1x7950 J463 T740 LS140	490	130	7923	51,0	155	70+	4000	8,3
RK-EU-PL15 1x9900 J464 T740 LS140	490	130	9891	67,2	147	70+	4000	8,3
RK-EU-PL15 1x11300 J465 T740 LS140	490	130	11255	78,4	144	70+	4000	8,3


*Tolerance range for optical and electrical data: -10%. Values apply to an ambient temperature of 25°C. RIKADA is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

OPTIONS AVAILABLE ON REQUEST:

LED	REFLECTOR AND OPTICS	CONTROL GEAR	CONNECTION	PROTECTION	COLOUR
T730	LS90	DALI	CBF3x1.5-N m ¹	II	RAL
T740		ADIM	CBF5x1.5-N m ¹		

¹ Please specify the length of outgoing cable before placing an order

LS90



LS140

