



RK-EU-PL09

Park and Street Lights



DESCRIPTION:	Pole shaped ground mounted LED luminaire Light distribution type: direct Optical system: lenses, clear polycarbonate diffuser, impact resistant Housing: aluminium Colour: dark grey, RAL7043
GENERAL DATA:	Mains voltage: 220-240V, 0/50-60Hz LED lifetime, h: 100000/L90B10 SDCM: 5 Protection class IEC: I Ingress protection code: IP66 Mechanical impact resistance: IK08 Operating temperature range, °C: ta -25...+40
INSTALLATION:	On the ground. Screw terminal, 3x1x1.5mm ²
ENVIRONMENT:	Outdoor
APPLICATION:	Park, public space

PRODUCT	DIAMETER, mm	HEIGHT, mm	LUMINAIRE OUTPUT*, lm	SYSTEM POWER*, W	SYSTEM EFFICACY*, lm/W	CRI	CCT*, K	WEIGHT, kg
RK-EU-PL09 1x5000 J673 T740 LS140	168	3500	5000	50,0	100	70+	4000	31,0
RK-EU-PL09 1x5000 J673 T740 LSM1	168	3500	5000	50,0	100	70+	4000	31,0

*Tolerance range for optical and electrical data: -10%. Values apply to an ambient temperature of 25°C. RIKADA is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

OPTIONS AVAILABLE ON REQUEST:

LED	REFLECTOR AND OPTICS	CONTROL GEAR
T730	LS140	DALI
T740	LSM1	

LS140

LSM1



