

RK-EU-WP09

Waterproof and Cleanroom Luminaires



DESCRIPTION: Surface mounted waterproof basic LED luminaire
Light distribution type: direct
Optical system: opal polycarbonate diffuser
Housing: polycarbonate
Colour: white

GENERAL DATA: Mains voltage: 220-240V, 50-60Hz
LED lifetime, h: 25000/L70B50
SDCM: 5
Protection class IEC: II
Ingress protection code: IP65
Mechanical impact resistance: IK07
Operating temperature range, °C:
ta -20...+40

INSTALLATION: On the ceiling or wall (mounting brackets included), or suspended.
Cable, 0.25m, 2x0.75mm²

ENVIRONMENT: Indoor

APPLICATION: Industry, warehouse, public place, parking area



PRODUCT	LENGTH, mm	WIDTH, mm	HEIGHT, mm	LUMINAIRE OUTPUT*, lm	SYSTEM POWER*, W	SYSTEM EFFICACY*, lm/W	CRI	CCT*, K	WEIGHT, kg
RK-EU-WP09 1x3600 D595 T740 OP	1200	60	35	3600	36,0	100	70+	4000	0,4
RK-EU-WP09 1x4800 D596 T740 OP	1500	60	35	4800	46,0	104	70+	4000	0,5

*Tolerance range for optical and electrical data: -10%. Values apply to an ambient temperature of 25°C. RIKADA is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

Note - luminaire is not suitable for frequent switching

OP

