


RK-EU-PL08

Park and Street Lights





DESCRIPTION: Pole-mounted LED park luminaire
Light distribution type: direct
Optical system: lenses, tempered glass diffuser, impact resistant
Housing: aluminium
Colour: light grey, RAL9006

GENERAL DATA: Mains voltage: 220-240V, 0/50-60Hz
LED lifetime, h: 100000/L90B10
SDCM: 5
Protection class IEC: I
Ingress protection code: IP66
Mechanical impact resistance: IK08
Operating temperature range, °C: ta -40...+40

INSTALLATION: With two screws on poles Ø60mm.
Cable, 3.0m, 3x0.75mm²

ENVIRONMENT: Outdoor

APPLICATION: Park, public space



PRODUCT	DIAMETER, mm	HEIGHT, mm	LUMINAIRE OUTPUT*, lm	SYSTEM POWER*, W	SYSTEM EFFICACY*, lm/W	CRI	CCT*, K	WEIGHT, kg
RK-EU-PL08 1x5050 J455 T740 LS140	500	235	5009	34,3	146	70+	4000	10,0
RK-EU-PL08 1x7100 J456 T740 LS140	500	235	7073	48,7	145	70+	4000	10,0
RK-EU-PL08 1x9700 J457 T740 LS140	500	235	9663	68,0	142	70+	4000	10,0

*Tolerance range for optical and electrical data: -10%. Values apply to an ambient temperature of 25°C. RIKADA is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

OPTIONS AVAILABLE ON REQUEST:

LED	COVERS	CONTROL GEAR	SENSORS	PROTECTION	COLOUR
T730	SHADE	DALI	PCA	II	RAL
T740		ADIM			

LS140

