


RK-EU-IN01

Inground Lights



DESCRIPTION: Ground-mounted LED luminaire
Light distribution type: direct
Optical system: frosted tempered glass diffuser, impact resistant
Housing: stainless steel
Colour: stainless-steel, brushed

GENERAL DATA: Mains voltage: 220-240V, 0/50-60Hz
LED lifetime, h: 50000/L80B10
SDCM: 3
Protection class IEC: I
Ingress protection code: IP67
Mechanical impact resistance: IK10
Operating temperature range, °C: ta -25...+40

INSTALLATION: In the ground. Cable, 1.0m, 3x1.5mm²

ENVIRONMENT: Outdoor

APPLICATION: Facade illumination, public space



PRODUCT	LENGTH, mm	WIDTH, mm	HEIGHT, mm	CUT-OUT, mm	LUMINAIRE OUTPUT*, lm	SYSTEM POWER*, W	SYSTEM EFFICACY*, lm/W	CRI	CCT*, K	WEIGHT, kg
RK-EU-IN01 1x450 J692 T840	430	115	105	410x105x110	431	5,3	81	80+	4000	3,1
RK-EU-IN01 1x550 J693 T840	430	115	105	410x105x110	529	6,7	79	80+	4000	3,1
RK-EU-IN01 1x800 J694 T840	630	115	105	610x105x110	754	9,3	81	80+	4000	4,6
RK-EU-IN01 1x950 J695 T840	630	115	105	610x105x110	926	11,1	83	80+	4000	4,6
RK-EU-IN01 1x1450 J696 T840	1050	115	105	1025x105x110	1401	16,5	85	80+	4000	7,2
RK-EU-IN01 1x1750 J697 T840	1050	115	105	1025x105x110	1721	19,9	86	80+	4000	7,2

*Tolerance range for optical and electrical data: -10%. Values apply to an ambient temperature of 25°C. RIKADA is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

AVAILABLE ACCESSORIES:



Product: Power supply connector I IP68
 2x3x2.5mm²

Description: Connection box IP68 filled with gel, "I" type, 2x3x2.5mm², 250V/6A, external cable diameter: 5,5-10mm, 1pcs

*For installation IP68 waterproof connectors are recommended



Product: Power supply connector T IP68
 3x3x2.5mm²

Description: Junction box IP68 filled with gel, "T" type, 3x3x2.5mm², 250V/16A, external cable diameter: 6,5-12mm, luminaire cable diameter: 5,5-10mm, 1pcs

*For installation IP68 waterproof connectors are recommended

OPTIONS AVAILABLE ON REQUEST:

LED	CONTROL GEAR
T830	DALI
T840	

STANDARD

