




RK-EU-HB09

High-bays



DESCRIPTION:	Suspended high-bay basic LED luminaire Light distribution type: direct Optical system: lenses Housing: aluminium Colour: black, RAL9017
GENERAL DATA:	Mains voltage: 100-240V, 50/60Hz LED lifetime, h: 85000/L80B10 SDCM: 5 Protection class IEC: I Ingress protection code: IP65 Mechanical impact resistance: IK10 Operating temperature range, °C: ta -30...+50
INSTALLATION:	Suspended. Supplied with suspension hook and out-going cable for easy mounting. Cable, 0.3m, 3x0.75mm2
ENVIRONMENT:	Indoor
APPLICATION:	Industry, warehouse, hall



PRODUCT	DIAMETER, mm	HEIGHT, mm	LUMINAIRE OUTPUT*, lm	SYSTEM POWER*, W	SYSTEM EFFICACY*, lm/W	CRI	CCT*, K	WEIGHT, kg
RK-EU-HB09 1x15000/12000/9000 J676 T840	265	158	9000/12000/15000	60/80/100	150	80+	4000	2,1
RK-EU-HB09 1x22500/18000/13500 J677 T840	265	158	13500/18000/22500	90/120/150	150	80+	4000	2,1
RK-EU-HB09 1x30000/24000/18000 J678 T840	300	160	18000/24000/30000	120/160/200	150	80+	4000	3,1
RK-EU-HB09 1x15000/12000/9000 J676 T840 DIM ZHAGA18	265	158	9000/12000/15000	60/80/100	150	80+	4000	2,0
RK-EU-HB09 1x22500/18000/13500 J677 T840 DIM ZHAGA18	265	158	13500/18000/22500	90/120/150	150	80+	4000	2,0
RK-EU-HB09 1x30000/24000/18000 J678 T840 DIM ZHAGA18	300	160	18000/24000/30000	120/160/200	150	80+	4000	2,2
RK-EU-HB09 1x15000 J676 T840 DALI	265	158	15000	100	150	80+	4000	2,0
RK-EU-HB09 1x22500 J677 T840 DALI	265	158	22500	150	150	80+	4000	2,0
RK-EU-HB09 1x30000 J678 T840 DALI	300	160	30000	200	150	80+	4000	2,2
RK-EU-HB09 1x15000/12000/9000 J676 T840 4EMG	265	158	9000/12000/15000	60/80/100	150	80+	4000	2,0
RK-EU-HB09 1x22500/18000/13500 J677 T840 4EMG	265	158	13500/18000/22500	90/120/150	150	80+	4000	2,0
RK-EU-HB09 1x30000/24000/18000 J678 T840 4EMG	300	160	18000/24000/30000	120/160/200	150	80+	4000	2,2

*Tolerance range for optical and electrical data: -10%. Values apply to an ambient temperature of 25°C. RIKADA is constantly developing and improving its products. The right is reserved to change any product specifications without prior notification

AVAILABLE ACCESSORIES:



Product: Power supply connector - IP66/ IP68, 3x1.5mm²

Description: Quick and easy to connect power supply and luminaire cable connector - IP66/IP68, 3x1.5mm², 450V/10A, 1pcs



Product: Sensor HBPIR ZHAGA 360 D12/12 DIM B

Description: PIR, Zhaga 18, 0-10V, IP65, 360°, d<12m, h<12m, black



Product: Remote control RC-100

Description: Remote control unit



Product: RK-EU-HB09 4EMG kit
External emergency version 3 hours

**note - RK-EU-HB09 4EMG kit available only for models RK-EU-HB09 4EMG models*

**note - Operating temperature range for Luminaires with RK-EU-HB09 4EMG kit, C: ta 0... +50*



Product: One-point High-bay Suspension MTG KIT, 1.5m
Description: One-point high bay suspension kit for lifting eye type mounts, 1.5 meter

Product: One-point High-bay Suspension MTG KIT, 3.0m
Description: One-point high bay suspension kit for lifting eye type mounts, 3.0 meter

Product: One-point High-bay Suspension MTG KIT, 5.0m
Description: One-point high bay suspension kit for lifting eye type mounts, 5.0 meter



Product: Sensor HBPIR ZHAGA 360 D20/12 DIM KRBLT B

Description: PIR, Zhaga 18, 0-10V KRBLT, IP65, 360°, d<20m, h<12m, black

OPTIONS AVAILABLE ON REQUEST:

CONNECTION

CBF3x1.5-N m^{1 2}

CBF5x1.5-N m^{1 2}

- 1 Please specify the length of outgoing cable before placing an order
- 2 For DALI option dimming range is 10 – 100 %

STANDARD

